

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name FORPRIME-DPM Comp B.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name FORPRIME-DPM, Comp. B

Article number: 20203.02

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Forcrete Ltd

6 Fitzmaurice Court Industrial Estate, Valley Side, Wymondham NR18 0NN

Tel: +441603455962

Mob: +447472483348

Information department:

Product Safety department: George Hunt Tel: +447472483348

E-Mail: sales@forcrete.co.uk

1.4 Emergency telephone number:

Tel: +447472483348

sales@forcrete.co.uk

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Acute Tox. 4 H332 Harmful if inhaled.

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 2 H361f Suspected of damaging fertility.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name FORPRIME-DPM Comp B.



Signal word Danger

Hazard-determining components of labelling:

3-aminomethyl-3,5,5-trimethylcyclohexylamine
benzyl alcohol
4-tert-butylphenol
m-phenylenebis(methylamine)
trimethylhexane-1,6-diamine
2,4,6-tris(dimethylaminomethyl)phenol
N-(3-(trimethoxysilyl)propyl)ethylenediamine
2-piperazin-1-ylethylamine
triethylenetetramine

Hazard statements

H332 Harmful if inhaled.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H361f Suspected of damaging fertility.
H411 Toxic to aquatic life with long lasting effects

Precautionary statements

P260 Do not breathe mist/vapours/spray.
P264 Wash thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312 IF SWALLOWED: Call a POISON CENTER if you feel unwell.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name FORPRIME-DPM Comp B.

3.2 Chemical characterisation: Mixtures Description: Mixture of the substances listed below with harmless additions.

Dangerous components [% w/w]:		
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-XXXX	benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	10-20%
CAS: 2855-13-2 EINECS: 220-666-8 Index number: 612-067-00-9 Reg.nr.: 01-2119514687-32-XXXX	3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	10-20%
CAS: 98-54-4 EINECS: 202-679-0 Reg.nr.: 01-2119489419-21-XXXX	4-tert-butylphenol Repr. 2, H361f; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315	10-20%
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50-XXXX	m-phenylenebis(methylamine) Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412	5-10%
CAS: 25620-58-0 EINECS: 247-134-8	trimethylhexane-1,6-diamine Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317	5-10%
CAS: 90-72-2 EINECS: 202-013-9 Index number: 603-069-00-0 Reg.nr.: 01-2119560597-27-XXXX	2,4,6-tris(dimethylaminomethyl)phenol Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1B, H317	≥2.5-<3%
CAS: 103-83-3 EINECS: 203-149-1 Index number: 612-074-00-7 Reg.nr.: 01-2119529232-48-XXXX	benzyl dimethylamine Flam. Liq. 3, H226; Acute Tox. 3, H331; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Aquatic Chronic 3, H412	≥1-≥2.5%
CAS: 1760-24-3 EINECS: 217-164-6	N-(3-(trimethoxysilyl)propyl)ethylenediamine Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1, H317	≥0.1-<1%
CAS: 61788-46-3 EINECS: 262-977-1 Index number: 612-285-00-4 Reg.nr.: 01-2119473798-17-XXXX	Amines, coco alkyl STOT RE 2, H373; Asp. Tox. 1, H304; Skin Corr. 1B, H314; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10); Acute Tox. 4, H302; STOT SE 3, H335	≥0.25-<1%
CAS: 140-31-8 EINECS: 205-411-0 Index number: 612-105-00-4 Reg.nr.: 01-2119471486-30-XXXX	2-piperazin-1-ylethylamine Acute Tox. 3, H311; Repr. 2, H361; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<1%
CAS: 90640-67-8 EINECS: 292-588-2 Index number: 612-059-00-5 Reg.nr.: 01-2119487919-13-XXXX	triethylenetetramine Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<1%

SVHC	
CAS: 98-54-4	4-tert-butylphenol

Additional information For the wording of the listed hazard phrases refer to section 16.

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name FORPRIME-DPM Comp B.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation Seek medical treatment in case of complaints.

After skin contact

If skin irritation continues, consult a doctor.

Wash immediately with water and soap and rinse thoroughly.

After eye contact Rinse opened eye for several minutes under running water. Then consult doctor.

After swallowing

Call a doctor immediately.

Drink plenty of water and provide fresh air. Call a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

In case of prolonged/repeated exposure or in high concentrations:

Coughing

Dazed

Respiratory distress (dyspnoea)

Gastro-intestinal symptoms

nausea

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

symptomatic treatment

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents Use firefighting measures that suit the environment.

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

May be released in case of fire

Carbon monoxide (CO)

Carbon dioxide

carbon monoxides

further harmful conflagration gases and fumes

5.3 Advice for firefighters

Protective equipment:

Wear self-contained breathing apparatus.

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name FORPRIME-DPM Comp B.

Wear full protective suit.

Put on breathing apparatus.

Additional information

Cool endangered containers with water spray jet.

Collect contaminated firefighting water separately. It must not enter drains.

Dispose of fire debris and contaminated firefighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Inform responsible authorities in case product reaches bodies of water or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well ventilated areas.

Ensure good ventilation/exhaust in workplaces.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers:

Store only in unopened original containers.

Prevent any penetration into the ground.

Information on storage in a common storage facility:

Store away from oxidising agents.

Store away from food.

Further information about storage conditions:

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name FORPRIME-DPM Comp B.

Store container in a well ventilated position.

Protect from frost.

Keep container tightly closed.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with limit values that have to be monitored at the workplace.

Additional information: The lists that were valid during compilation were used as a basis.

8.2 Exposure controls

Personal protective equipment

General protective and hygienic measures

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

Respiratory equipment:

Filter A (brown)

Only use ambient air independent respiratory equipment in pits, shafts and silos!

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case

of intensive or longer exposure, use self-contained respiratory protection equipment.

Protection of hands:

Long cuffed gloves

Protective gloves.

The glove material must be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 374 part III are not performed under practical

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name FORPRIME-DPM Comp B.

conditions. Therefore, a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break through time must be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Tightly sealed safety glasses.

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties
General Information
Appearance:
Form: Fluid
Colour: clear
Odour: Amine-like
Odour threshold: Not determined.
pH-value: Not determined.
Change in condition
Melting point/freezing point: Not determined
Initial boiling point and boiling range: >100 °C
Flash point: >100 °C (Setaflash)
Inflammability (solid, gaseous) Not applicable.
Ignition temperature: not applicable
Decomposition temperature: Not determined.
Self-inflammability: Product is not self-igniting.
Explosive properties: Product is not explosive.
Explosive Limits:
Lower: Not determined.
Upper: Not determined.
Vapour pressure: Not determined.
Density at 20 °C: 0.97 g/cm ³
Relative density Not determined.
Vapour density Not determined.
Evaporation rate Not determined.
Solubility in / Miscibility with Water: Not miscible or difficult to mix
Distribution coefficient (n-octanol/water): Not determined.
Viscosity:
dynamic at 20 °C: 200 mPas
kinematic: Not determined.
Solvent separation test < 3 %
9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name FORPRIME-DPM Comp B.

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

Avoid: heat, flames, sparks

10.3 Possibility of hazardous reactions No dangerous reactions known

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

None if used properly.

None if stored properly.

SECTION 11: Toxicological information

11.1 Information on toxicological effects Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:

CAS: 100-51-6 benzyl alcohol

Oral LD50 1,230 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

CAS: 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Oral LD50 1,030 mg/kg (rat)

Dermal LD50 1,840 mg/kg (rabbit)

CAS: 98-54-4 4-tert-butylphenol

Oral LD50 2,951 mg/kg (rat)

Dermal LD50 2,288 mg/kg (rabbit)

Skin corrosion/irritation:

Causes severe skin burns and eye damage.

Serious eye damage/irritation:

Causes serious eye damage.

Sensitisation:

May cause an allergic skin reaction.

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity:

Suspected of damaging fertility.

STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name FORPRIME-DPM Comp B.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark: Toxic for fish

Additional ecological information:

General notes:

Do not allow undiluted or non-neutralised product to reach the sewage system or receiving waters.

Also toxic for fish and plankton in bodies of water.

Toxic for aquatic organisms

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

Recommendation

Not hardened material must be disposed of as hazardous waste according to official regulations.

Hardened product remains may be disposed of as building rubble or put into household garbage.

The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

European waste catalogue

20 01 28 paint, inks, adhesives and resins other than those mentioned in 20 01 27

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN-Number




ADR, IMDG, IATA UN2735

14.2 UN proper shipping name

ADR	2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine)),
IMDG	ENVIRONMENTALLY HAZARDOUS POLYAMINES, LIQUID, CORROSIVE, N.O.S. (mphenylenebis(methylamine)),
IATA	MARINE POLLUTANT POLYAMINES, LIQUID, CORROSIVE, N.O.S. (mphenylenebis(methylamine))
14.3 Transport hazard class(es)	

Safety data sheet
according to 1907/2006/EC, Article 31

Trade name FORPRIME-DPM Comp B.

<p>ADR</p>  <p>Class Label</p> <p>IMDG</p>  <p>Class Label</p> <p>IATA</p>  <p>Class Label</p>	<p>8 (C7) Corrosive substances. 8</p> <p>8 Corrosive substances. 8</p> <p>8 Corrosive substances. 8</p>
<p>14.4 Packing group ADR, IMDG, IATA</p>	<p>II</p>
<p>14.5 Environmental hazards: Marine pollutant: Special marking (ADR):</p>	<p>Yes Symbol (fish and tree) Symbol (fish and tree)</p>
<p>14.6 Special precautions for user hazard identification number: EMS Number: Segregation groups Stowage Category Segregation Code</p>	<p>Warning: Corrosive substances. 80 F-A,S-B Alkalis A SG35 Stow "separated from" SGG1-acids</p>
<p>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</p>	<p>Not applicable.</p>
<p>Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category</p>	<p>1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml 2</p>

Safety data sheet
according to 1907/2006/EC, Article 31

Trade name FORPRIME-DPM Comp B.

IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (M-PHENYLENEBIS(METHYLAMINE)), 8, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

National regulations

Other regulations, limitations and prohibition ordinances

APME document: "Epoxy resins and curing agents: Toxicology, working safety, environment."

Substances of very high concern (SVHC) according to REACH, Article 57

CAS: 98-54-4 4-tert-butylphenol

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Delivery specifications are found in the respective Technical Information Sheets.

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name FORPRIME-DPM Comp B.

H335 May cause respiratory irritation.
H361 Suspected of damaging fertility or the unborn child.
H361f Suspected of damaging fertility.
H372 Causes damage to organs through prolonged or repeated exposure.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Department issuing data specification sheet: Product Safety department / EHS

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
Repr. 2: Reproductive toxicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3