Safety data sheet

according to 1907/2006/EC, Article 31

Trade name FORPRIME-HB Comp A.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name FORPRIME-HB, Comp. A Article number: 20207.01

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of preparation:

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Forcrete Ltd

6 Fitzmaurice Court Industrial Estate, Valley Side, Wymondham NR18 0NN Tel: +441603455962

Mob: +447472483348

Information department:

Product Safety department: George Hunt Tel: +447472483348

- E-Mail: sales@forcrete.co.uk
- 1.4 Emergency telephone number:

Tel: +447472483348

sales@forcrete.co.uk

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

Trade name FORPRIME-HB Comp A. Hazard pictograms



Signal word Warning

Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

bisphenol F-(epichlorhydrin); epoxy resin(number average molecular weight<700) hexandiol diglycidylether

Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Trade name FORPRIME-HB Comp A.

Description: Mixture of the substances listed below with harmless additions.

Dangaraus components:		
Dangerous components:		
CAS: 25068-38-6	reaction product: bisphenol-A-(epichlorhydrin); epoxy	20-40%
NLP: 500-033-5	resin (number average molecular weight ≤ 700)	
Index number: 603-074-00-8	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2,	
Reg.nr.: 01-2119456619-26-XXXX	H319; Skin Sens. 1, H317	
CAS: 7727-43-7	barium sulphate, natural	20-40%
EINECS: 231-784-4	substance with a Community workplace exposure	
	limit	
CAS: 68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	5-10%
EINECS: 271-846-8	Skin Irrit. 2, H315; Skin Sens. 1, H317	
Index number: 603-103-00-4		
Reg.nr.: 01-2119485289-22-XXXX		
CAS: 28064-14-4	bisphenol F-(epichlorhydrin); epoxy resin(number	5-10%
NLP: 500-006-8	average molecular weight<700)	
Reg.nr.: 01-2119454392-40-XXXX	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin	
-	Sens. 1, H317	
CAS: 16096-31-4	hexandiol diglycidylether	≤0.5%
EINECS: 240-260-4	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1,	
Reg.nr.: 01-2119463471-41-XXXX	H317; Aquatic Chronic 3, H412	

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

If symptoms occur or in case of doubt, seek medical attention. In case of unconsciousness, do not administer anything orally.

After inhalation

Supply fresh air and call for doctor for safety reasons. In case of unconsciousness bring patient into stable side position for transport.

After skin contact

If skin irritation continues, consult a doctor.

Wash immediately with water and soap and rinse thoroughly.

After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing

Rinse out mouth immediately with plenty of water and administer plenty of water in small swallows (diluting effect).

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name FORPRIME-HB Comp A.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam. Use fire fighting measures that suit the environment.

5.2 Special hazards arising from the substance or mixture

May be released in case of fire

Carbon monoxide (CO) further harmful conflagration gases and fumes

5.3 Advice for firefighters

Protective equipment: Wear self-contained breathing apparatus.

Wear full protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow to enter the ground/soil.

Do not allow product to reach sewage system or water bodies.

Inform responsible authorities in case product reaches bodies of water or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of contaminated material as waste according to item 13. Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well ventilated areas. Ensure good ventilation/exhaust in workplaces. Avoid the formation of aerosols.

Safety data sheet

according to 1907/2006/EC, Article 31

Trade name FORPRIME-HB Comp A.

7.2 Conditions for safe storage, including any incompatibilities
Storage
Requirements to be met by storerooms and containers: Prevent any penetration into the ground.
Information on storage in a common storage facility: Store away from food.
Further information about storage conditions:
Store container in a well ventilated position.
Protect from frost.

Keep container tightly closed.

7.3 Specific end use(s) No further relevant information available

SECTION 8: Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

Components with limit values that require monitoring at the workplace:

CAS: 7727-43-7 barium sulphate, natural

WEL Long-term value: 10* 4** mg/m³

*inhalable dust **respirable dust Additional information: The lists that were valid during compilation were used as a basis.

8.2 Exposure controls

Personal protective equipment

General protective and hygienic measures

Do not eat, drink or smoke while working.

Use skin protection cream for preventive skin protection.

Keep away from food, beverages and animal feed.

Immediately remove soiled, saturated clothing.

Wash hands before pauses and after work.

Avoid contact with eyes and skin.

Respiratory equipment:

Filter A (brown)

Only use ambient air independent respiratory equipment in pits, shafts and silos!

In case of brief exposure or low pollution load, use respiratory protection equipment with filter. In case of intensive or longer exposure, use self-contained respiratory protection equipment.

Protection of hands:

Long cuffed gloves

Trade name FORPRIME-HB Comp A.

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the

degradation

Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several

substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical

conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Tightly sealed safety glasses.

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties		
General Information		
Anno-ronco:		
Appearance: Form: Liquid		
Colour: Grey		
Odour: Odourless		
Odour threshold: Not determined.		
pH-value: Not determined.		
Change in condition		
Melting point/freezing point: Not determined		
Initial boiling point and boiling range: Not determined		
Flash point: >100c		
Inflammability (solid, gaseous) Not applicable.		
Ignition temperature: Not applicable.		
Decomposition temperature: Not applicable.		
Self-inflammability: Product is not self-igniting.		
Explosive properties: Product is not explosive.		
Explosive Limits:		
Lower: Not determined.		
Upper: Not determined.		
Vapour pressure at 20c: Not determined		
Density at 20 °C: ca. 1.73 g/cm ³		

Trade name FORPRIME-HB Comp A.

Relative density: Not determined.		
Vapour density: Not determined.		
Evaporation rate: Not determined.		
Solubility in / Miscibility with Water: miscible		
Distribution coefficient (n-octanol/water): Not determined.		
Viscosity:		
Dynamic at 20c: 3100 mPas		
Kinematic: Not determined.		
Solvent separation test: < 3%		
9.2 Other information No further relevant information available.		

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if handled and stored according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products:

None if used properly.

None if stored properly.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity: Based on available data, the classification criteria are not met.

LD/LC50 values that are relevant for classification:

CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

Oral LD50 >10,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rat)

Skin corrosion/irritation: Causes skin irritation.
Serious eye damage/irritation: Causes serious eye irritation.
Sensitisation: May cause an allergic skin reaction
Experience with humans: Based on available data, the classification criteria are not met.
Germ cell mutagenicity: Based on available data, the classification criteria are not met.
Carcinogenicity: Based on available data, the classification criteria are not met.
Reproductive toxicity: Based on available data, the classification criteria are not met.

Trade name FORPRIME-HB Comp A.

STOT-single exposure: Based on available data, the classification criteria are not met.STOT-repeated exposure: Based on available data, the classification criteria are not met.Aspiration hazard: Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxical effects:

Remark: Toxic to fish

Additional ecological information: General notes:

Do not allow product to reach ground water, bodies of water or sewage system.

Hazardous to drinking water even if small quantities leak into soil.

Also toxic for fish and plankton in bodies of water.

Toxic for aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

Recommendation

Not hardened material must be disposed of as hazardous waste according to official regulations. Hardened product remains may be disposed of as building rubble or put into household garbage. The given refuse codes are recommendations based upon the intended use of the product. Because of special use and disposal conditions at the user's, other codes may apply under other conditions.

European waste catalogue

20 01 28*- paint, inks, adhesives and resins other than those mentioned in 20 01 27

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleaning agent: Water, if necessary with cleaning agent.

SECTION 14: Transport information

14.1 UN-Number	
ADR, IMDG, IATA UN3082	UN3082
4.2 UN proper shipping name 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE,	
ADR	LIQUID, N.O.S. (Epoxy Resin (reaction product: bisphenol

Trade name FORPRIME-HB Comp A.

	A-(epichlorhydrin) (number average molecular weight ≤ 700)))	
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,	
	N.O.S. (Epoxy Resin (reaction product: bisphenol A-	
	(epichlorhydrin) (number average molecular weight ≤	
	700))), MARINE POLLUTANT	
ΙΑΤΑ	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,	
	N.O.S. (Epoxy Resin (reaction product: bisphenol A-	
	(epichlorhydrin) (number average molecular weight ≤	
	700)))	
14.3 Transport hazard class(es)		
ADR		
Class		
Label	9 (M6) Miscellaneous hazardous substances and articles.	
	9	
IMDG, IATA		
\mathbf{A} \wedge		
Class		
Label	9 (M6) Miscellaneous hazardous substances and articles.9	
14.4 Packing group		
ADR, IMDG, IATA		
14.5 Environmental hazards:	Product contains environmentally hazardous substances:	
	Epoxy Resin (reaction product: bisphenol A-	
	(epichlorhydrin) (number average molecular weight ≤	
	700))	
Marine pollutant:	Symbol (fish and tree)	
Special marking (ADR):	Symbol (fish and tree)	
Special marking (IATA):	Symbol (fish and tree)	
14.6 Special precautions for user	Warning: Miscellaneous hazardous substances and	
	articles.	
hazard identification number:	90	
EMS Number:	F-A,S-F	
Stowage Category	A	
14.7 Transport in bulk according to Annex II of	Not applicable.	
Marpol and the IBC Code		
Transport/Additional information:	5L	
ADR	Code: E1	
Limited quantities (LQ)	Maximum net quantity per inner packaging: 30 ml	
Excepted quantities (EQ)	Maximum net quantity per outer packaging: 1000 ml	
Transport category	3	
IMDG		
Limited quantities (LQ)	5L	
Excepted quantities (EQ)	Code: E1	

Trade name FORPRIME-HB Comp A.

	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
	LIQUID, N.O.S. (EPOXY RESIN (REACTION PRODUCT:
	BISPHENOL A- (EPICHLORHYDRIN) (NUMBER AVERAGE
	MOLECULAR WEIGHT ≤ 700))), 9, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

National regulations

Other regulations, limitations and prohibition ordinances

APME document: "Epoxy resins and curing agents: Toxicology, working safety, environment."

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Delivery specifications are found in the respective Technical Information Sheets.

This data is based on our present state of knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally valid contractual relationship.

Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008 Calculation method

Department issuing data specification sheet: Product Safety department / EHS

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

Trade name FORPRIME-HB Comp A.

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3