



FORCRETE.

EVERY SURFACE MATTERS

FORSHIELD-FX

P 01603 455962

E sales@forcrete.co.uk

W www.forcrete.co.uk

PRODUCT DESCRIPTION

One component thixotropic paste for pore-filling & creating effects onto microcement, can be used with FX pigments or on its own.

MATERIAL FEATURES

- Gloss
- Slip-resistant
- UV resistant
- Water vapour diffusion capable

KEY INFORMATION



USE
NEAT



TECHNICAL DATA

Product type: Sealer

User time: (+20 °C) 60 minutes

Appearance: Clear liquid

Chemical Nature:

Shelf Life: 12 months

Consumption: 70g – 80g per m²

FORSHIELD-FX APPLICATION INSTRUCTIONS

1. SURFACE PREPARATION

The substrate must be firm, free of dust, oil, grease, rubber marks and other substances that could interfere with adhesion.

2. MIXING INSTRUCTIONS

If adding pigment, mix thoroughly with a slow-speed electric mixer (approx. 300 - 400 rpm).

Mix for at least 3 minutes.

3. APPLICATION

Apply the material to the surface and trowel to the required finish.

Consumption rate: 70g – 80g /m²

4. SPECIAL PRECAUTIONS

- For professional use only
 - Do not apply below +5 °c or above +25 °c
 - Keep out of reach of children
 - Dispose of waste in accordance with current legislation
-

5. CLEANING OF TOOLS

Clean tools, equipment, and any splashed material immediately with water while still fresh. Take suitable protective and waste disposal measures when cleaning.